CESO Regulation No. 385-1-6	Department of the Army U.S. Army Corps of Engineers Washington, DC 20314-1000	ER 385-1-6 12 May 89
	Safety	
	STANDARD COLOR AND MARKINGS FOR HARD HATS	
	Distribution Restriction Statement Approved for public release; distribution is unlimited.	

DEPARTMENT OF THE ARMY U. S. Army Corps of Engineers Washington, DC 23-0314-1000

CEEC-S

Regulation No. 385-1-6

12 May 1989

Safety STANDARD COLOR AND MARKINGS FOR HARD HATS

- This regulation prescribes the color and markings for hard hats used within the U.S. Army Corps of Engineers.
- 2. Applicability. This directive is applicable to call Corps of Engineers employees who, because of occupational exposure, are required to wear hard hats.
- 3. References.
 - a. ER 385-1-40
 - b. EM 385-1-1
- The shell of hard hats will be write. No paint shall be used which will reduce the dielectric or impact protection by attacking and softening the shell material.
- 5. Markings. A one-inch band of red reflective material will be placed along the base of the hat crown with a five-inch break in front. A red Corps of Engineers insignia will be centered horizontally at the front of the hat with the base of the insignia approximately 3/4-inch above the base of the hat crown. Key personnel will have their name placed above the insignia and their organizational title below the insignia: name and title identification is optional for other employees. Military rank of active duty personnel may precede their name. Name and title will be embossed on tape. Local use of the sides of hard hats for safety-oriented decals is authorized. The integrity of the hat shell will not be destroyed by drilling holes for mounting military or other insignia.

FOR THE COMMANDER:

ALBERT J. GENETTI, JR. Colonel, Corps of Engineers Chief of Staff

This regulation supersedes ER 385-1-6 dated 24 June 1966.