

CB-534B CATERPILLER, DUEL STEEL ROLLER
HOT WEATHER/DESERT OPERATION

This abbreviated checklist is not to be used as a replacement for the -10 series Tech Manuals or any other PMCS guide.

FM 90-3, DESERT OPERATIONS contains detailed instructions for living and working in the desert.

TM 5-3895-379-10 contains detailed PMCS instructions for proper maintenance and operation.

NOTE: A very high standard of maintenance is essential to long term operation under conditions of extreme heat. High temperature can cause early failure of systems. Constant checking is necessary to prevent failures.

ENGINE OPERATION

1. Watch engine and hydraulic oil temperature
2. and temperature warning indicator light.
3. If any warning message or oil levels are ignored, damage may result.
4. Check oil levels frequently.
5. Follow proper engine cool down and shutdown procedures.
6. Make sure all air inlets are kept clear and sealed to permit cooling.
7. Check all hoses and fittings frequently to insure proper fit.
8. Inspect Cooling Fan Assemblies.
9. Remove packed sand from engine compartment.
10. Start up vehicles regularly to prevent discharge of batteries.
11. Gen/ALT belt tension.
12. Fluid levels correct to prevent heat build up
13. Oil cooler filter clean.

Approved for public release: distribution is unlimited

Distributor: U.S Training Support Center

March 2006

CB-534B CATERPILLER, DUEL STEEL ROLLER

ENGINE OPERATION (continued)

14. Clean air filter and dust boot
15. Keep Radiator fins clean of dust and debris
16. Keep mud and dirt cleaned off to reduce heat build up.
17. Fuel/water sediment bowl/filter drained
18. Use of high temp grease, to reduce thinning from heat
19. Clean up oil spills/grease to prevent dirt build up and heat retention.
20. Look at parts most affected by heat (belts, hoses and other rubber parts).
21. Ensure engine cooling fan blades are turned to the proper direction for
22. hot weather use on vehicles having this option

BATTERIES

1. Battery specific gravity must be changed to adjust for heat.
2. Watch ELECTRICAL SYSTEM voltmeter closely.
3. Keep batteries full, but do not overfill.

OPTICS

1. Under extreme dust conditions, check air cleaner service indicator every 1/2 hour of operation.
2. Lubricate suspension items daily, and clean grease fittings.
3. Reduce sand ingestion by stretching nylon stockings over air cleaners.
4. Check lubrication orders and TM's for the correct viscosity of lubricants for higher temperatures.
5. Clean sand and dirt away from vehicle.